GM 315 S 4

GAMAK

شركة الأندلس التجارية
Al Andalos Trading Co

3-Phase 400 V (Δ) 50 Hz

Duty Type	: S1
Degree of protection	: IP 55 (TEFC)
Insulation class	: F (155 °C)
Temp rise	: Class B (80K)
Mounting Design	: B3



ELECTRICAL DESIGN

Rated output (kW)	: 110
Speed (rpm)	: 1485
Rated current (A)	: 195
Torque – Mn (Nm)	: 707
Cos φ	: 0.86

	4/4	3/4	1/2
Efficiency %	: 94.5	94.5	93.8

Moment of inertia J (kgm)² : 2.1

Direct On Line

Locked rotor Current – Ia (A)	: 1365
Ia / In	: 7.0
Locked rotor Torque – Ma (Nm)	: 1626
Ma / Mn	: 2.3

Y / Δ Starting

Locked rotor Current – Ia (A)	: 449
Ia / In	: 2.3
Locked rotor Torque – Ma (Nm)	: 495
Ma / Mn	: 0.7
Breakdown Torque – Mk (Nm)	: 1838
Mk / Mn	: 2.6

MECHANICAL DESIGN

Frame	: Cast Iron
End shields	: Cast Iron
Cooling fan	: Plastic
Terminal box	: Aluminium
Cable gland	: Pg 48
No of cable glands	: 2

Bearing Arrangement

	Drive End	Non Drive End
Standard design	6318 C3	6318 C3
Reinforced design	NU 318 E	6318 C3

Noise Level (dB-A)	: 74
Paint	: RAL 7031- Grey
Approximate weight (kg)	: 784



DIMENSIONS

Dimensions of foot mounted motors for mounting arrangement : B3, B6, B7, B8, B15, V5, V6

H	HD ~	HA	A	AA	AB	ØAC	ØAK	K	K1	B	B'	BA	BA'	BB	L ~	LC	LK ~	C	E EA	DB DC	ØD ØDA	GA GC	FxGD FAXGF
315	825	50	508	125	620	614	51	28	-	406	-	115	166	550	1150	1330	1227	216	170	M20	85	90	22X14

* Efficiencies are calculated according to indirect method where the additional load losses are determined from exact measurements at different load points.

contact:
Mob:00201022621584/00201092425789
Email:info@andalos-trading.com
website:www.andalos-trading.com

Egypt-Giza-of October City
Lelat Alqader-Almaged Center